

(12) **United States Patent**
Sanso et al.

(10) **Patent No.:** **US 11,348,399 B1**
(45) **Date of Patent:** **May 31, 2022**

(54) **MEDSAFE MEDICATION DISPENSING AND MONITORING SYSTEM**

(71) Applicants: **David J Sanso**, Morrison, CO (US);
David W Sanso, Morrison, CO (US)

(72) Inventors: **David J Sanso**, Morrison, CO (US);
David W Sanso, Morrison, CO (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 141 days.

(21) Appl. No.: **16/408,185**

(22) Filed: **May 9, 2019**

Related U.S. Application Data

(60) Provisional application No. 62/669,524, filed on May 10, 2018.

(51) **Int. Cl.**
G07F 17/00 (2006.01)
G16H 20/13 (2018.01)

(52) **U.S. Cl.**
CPC **G07F 17/0092** (2013.01); **G16H 20/13** (2018.01)

(58) **Field of Classification Search**
CPC G07F 17/0092; G16H 20/13
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,573,606 A * 3/1986 Lewis A61J 7/0481
221/15
5,472,113 A * 12/1995 Shaw A61J 7/0084
221/15

5,582,323 A * 12/1996 Kurtenbach A61J 7/0481
221/2
5,609,268 A * 3/1997 Shaw A61J 7/0084
221/2
5,915,589 A * 6/1999 Lim A61J 7/0481
221/3
6,330,957 B1 * 12/2001 Bell-Greenstreet ... A61J 7/0481
221/120
6,510,962 B1 * 1/2003 Lim A61J 7/0481
221/15
8,068,934 B2 * 11/2011 Saltsov A61J 7/0084
700/242
8,195,330 B2 * 6/2012 Coe G07F 11/54
700/243
2006/0058724 A1 * 3/2006 Handfield A61J 7/0076
604/20
2008/0203107 A1 * 8/2008 Conley G07F 11/16
221/1
2012/0006847 A1 * 1/2012 Coe A61J 7/0481
222/52
2012/0259456 A1 * 10/2012 Saltsov A61J 7/0084
700/236
2014/0277702 A1 * 9/2014 Shaw A61J 7/0481
700/232
2018/0039756 A1 * 2/2018 Phipps G06F 21/6245

* cited by examiner


Primary Examiner — Michael Collins

(74) *Attorney, Agent, or Firm* — Luis Figarella

(57) **ABSTRACT**

A medication storage and dispensing system that includes a plurality of cavities that can be used to securely store and dispense pills and other medications in a secure, traceable and controlled environment. The system allows for the secure transport and dispensing, while allowing the tracking of inventory. The system provides reminders of when the medication should be taken.

1 Claim, 13 Drawing Sheets






Figure 1




Figure 2




Figure 3




Figure 4




Figure 5




Figure 6




Figure 7




Figure 8




Figure 9




Figure 10




Figure 11




Figure 12




Figure 13

MEDSAFE MEDICATION DISPENSING AND MONITORING SYSTEM

CROSS-REFERENCE TO RELATED APPLICATIONS

This application claims priority to U.S. Provisional patent application Ser. No. 62/669,524 titled "MEDsafe Medication Monitoring System", filed on May 10, 2018 the disclosure of which is herein incorporated by reference in its entirety.

PATENTS CITED

The following documents and references are incorporated by reference in their entirety, Kraft et al (WO 2013/033033), Lohman (U.S. Pat. No. 9,465,918) and Denny et al (U.S. Pat. Pub. No. 2015/0251839), Villegas Estrada (U.S. Pat. Pub. No. 2010/0147867), Schiff et al (U.S. Pat. Pub. No. 2018/0360693), Aby-Eva (U.S. Pat. Pub. No. 2014/0102859) and Baarman et al (U.S. Pat. Nos. 9,218,458 and 9,597,261).

FIELD OF THE INVENTION

The present invention relates to a system and method for the safe and authorized transport, storage and dispensing of medication, and for the access and dispensing of said medication only to approved and/or authorized parties.

DESCRIPTION OF THE RELATED ART

Over 10.3 million people used prescription opioids without a prescription in 2014. In 2016, 16 people died every day from opioid related overdoses, and 11.5 MM people misused prescription opioids. From July 2016 through September 2017 Opioid overdoses increased 30% in 45 states.

It can be difficult for doctors and health specialists to monitor patients' use of prescription drugs and supplements, particularly of opioids. Within family groups, sometimes unauthorized access to one patient's prescription by someone else, creates dangers and often illegal behavior. What is needed is a safe way in which to control, store and dispense addictive substances.

SUMMARY OF THE INVENTION

This section is for the purpose of summarizing some aspects of the present invention and to briefly introduce some preferred embodiments. Simplifications or omissions may be made to avoid obscuring the purpose of the section. Such simplifications or omissions are not intended to limit the scope of the present invention.

In one aspect the invention is about a controlled access medication dispensing system comprising a tamper-resistant (possibly tamper-proof) medication storage and dispensing unit equipped with internal medication storage and dispensing components, one or more dispensing openings and electronic interface components to control said internal medication component, including storing patient prescription, patient identification and stored medication information by authorized medical authorities or personnel. In another aspect, said dispensing units is comprised of an enclosed wheel within a housing, wherein said wheel is mechanically linked with wheel rotation components, said wheel having two or more cavities, so that rotation of said wheel by said rotation components causes the contents to come out through one or more dispensing slots. In yet

another aspect, said wheel rotation components are selected from a combination of one or more of: a worm drive motor, stepper motor, servo motor, mechanical clock mechanism or such other, said rotation component is coupled to one or more gearing teeth on said wheel and said wheel can only be moved while said mechanism is engaged. In another aspect, there is a dispensing sensor on said dispensing slot. In yet another aspect, said dispensing unit is sealed.

In another aspect a control and monitoring unit having one or more user identification (ID) confirmation components, system interface electronic components and network interface components for interfacing to one or more of said dispensing units and operation of said medication dispensing and storage portion is limited to those authorized by medical authorities. In yet another aspect, said user identification (ID) confirmation components are selected from one or more of the group comprised of: biometrics for face recognition, fingerprint recognition and/or voice recognition, Global Positioning (GPS) location, Cellular/Wireless/Internet location, password entry, two factor authentication, Personal Identification Numbers (PIN) entry or authorized personnel interaction via voice/video, said system interface electronic components are selected from one or more of the group comprised of: wired or wireless electronics including power, communication and/or interface and said network interface electronic components are selected from one or more of the group comprised of: IoT, RFID, Internet protocols, Wi-Fi, Bluetooth, email, 4G, 5G, SMS text, or messaging app (e.g. Telegram, WhatsApp, etc.). In another aspect said network interface is carried over a secure channel. In yet another aspect a refilling unit configured to drop medication via the dispensing unit's slot and automatically advancing the dispensing wheel within the dispensing unit. In yet another aspect said dispensing unit is lockable and access to said medication storage portion is limited to authorized medical authorities. In yet another aspect a refilling unit configured to drop medication via the dispensing unit's slot and automatically advancing the dispensing wheel within the dispensing unit.

In another aspect, the invention is about a method for controlled access medication dispensing, said method comprising providing a tamper-resistant (possibly tamper-proof) medication storage and dispensing unit equipped with internal medication storage and dispensing components, one or more dispensing openings and electronic interface components to control said internal medication component, including storing patient prescription, patient identification and stored medication information by authorized medical authorities or personnel. In yet another aspect said dispensing units is comprised of an enclosed wheel within a housing, wherein said wheel is mechanically linked with wheel rotation components, said wheel having two or more cavities, so that rotation of said wheel by said rotation components causes the contents to come out through one or more dispensing slots. In another aspect said wheel rotation components are selected from a combination of one or more of: a worm drive motor, stepper motor, servo motor, mechanical clock mechanism or such other, said rotation component is coupled to one or more gearing teeth on said wheel and said wheel can only be moved while said mechanism is engaged. In yet another there is a dispensing sensor on said dispensing slot. In another aspect said dispensing unit is sealed. In another aspect providing a control and monitoring unit having one or more user identification (ID) confirmation components, system interface electronic components and network interface components for interfacing to one or more of said dispensing units and wherein operation

of said medication dispensing and storage portion is limited to those authorized by medical authorities.

Other features and advantages of the present invention will become apparent upon examining the following detailed description of an embodiment thereof, taken in conjunction with the attached drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 shows an overall view of a proposed Medsafe monitoring system, according to an exemplary embodiment of the invention.

FIG. 2 shows the two primary components of a proposed Medsafe monitoring system, according to an exemplary embodiment of the invention.

FIG. 3 shows the control unit of a proposed Medsafe monitoring system, according to an exemplary embodiment of the invention.

FIG. 4 shows a storage and dispensing unit of a proposed Medsafe monitoring system, according to an exemplary embodiment of the invention.

FIG. 5 shows an exploded interior view of a proposed Medsafe monitoring system, according to an exemplary embodiment of the invention.

FIG. 6 shows details of the dispensing wheel of a proposed Medsafe monitoring system, according to an exemplary embodiment of the invention.

FIG. 7 shows an internal view of a proposed Medsafe monitoring system, according to an exemplary embodiment of the invention.

FIG. 8 shows a side view of a proposed Medsafe monitoring system, according to an exemplary embodiment of the invention.

FIG. 9 shows a perspective view of a proposed re-filling unit, according to an exemplary embodiment of the invention.

FIG. 10 shows a side view of a proposed re-filling unit, according to an exemplary embodiment of the invention.

FIGS. 11 and 12 show proposed all-in-one Medsafe monitoring systems, according to exemplary embodiments of the invention.

FIG. 13 shows a flowchart of the system operation, according to an exemplary embodiment of the invention.

The above-described and other features will be appreciated and understood by those skilled in the art from the following detailed description, drawings, and appended claims.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

This section is for the purpose of summarizing some aspects of the present invention and to briefly introduce some preferred embodiments. Simplifications or omissions may be made to avoid obscuring the purpose of the section. Such simplifications or omissions are not intended to limit the scope of the present invention.

To provide an overall understanding of the invention, certain illustrative embodiments and examples will now be described. However, it will be understood by one of ordinary skill in the art that the same or equivalent functions and sequences may be accomplished by different embodiments that are also intended to be encompassed within the spirit and scope of the disclosure. The compositions, apparatuses, systems and/or methods described herein may be adapted and modified as is appropriate for the application being addressed and that those described herein may be employed

in other suitable applications, and that such other additions and modifications will not depart from the scope hereof.

Simplifications or omissions may be made to avoid obscuring the purpose of the section. Such simplifications or omissions are not intended to limit the scope of the present invention. All references, including any patents or patent applications cited in this specification are hereby incorporated by reference. No admission is made that any reference constitutes prior art. The discussion of the references states what their authors assert, and the applicants reserve the right to challenge the accuracy and pertinence of the cited documents. It will be clearly understood that, although a number of prior art publications are referred to herein, this reference does not constitute an admission that any of these documents form part of the common general knowledge in the art.

As used in the specification and claims, the singular forms “a”, “an” and “the” include plural references unless the context clearly dictates otherwise. For example, the term “a transaction” may include a plurality of transaction unless the context clearly dictates otherwise. As used in the specification and claims, singular names or types referenced include variations within the family of said name unless the context clearly dictates otherwise.

Certain terminology is used in the following description for convenience only and is not limiting. The words “lower,” “upper,” “bottom,” “top,” “front,” “back,” “left,” “right” and “sides” designate directions in the drawings to which reference is made, but are not limiting with respect to the orientation in which the modules or any assembly of them may be used.

It is acknowledged that the term ‘comprise’ may, under varying jurisdictions, be attributed with either an exclusive or an inclusive meaning. For the purpose of this specification, and unless otherwise noted, the term ‘comprise’ shall have an inclusive meaning—i.e. that it will be taken to mean an inclusion of not only the listed components it directly references, but also other non-specified components or elements. This rationale will also be used when the term ‘comprised’ or ‘comprising’ is used in relation to one or more steps in a method or process.

Referring to FIGS. 1-2 we see an overall view 100 of a proposed Medsafe monitoring system, comprised of a primary control unit 102 and one or more medication storage and dispensing units 104. The combination of both units 102/104 provides a secure, tamper-proof system that allows for the distribution, storage and secure dispensing of one or more medications.

The MEDsafe Lifesaver would allow for distribution of medication (in all forms including pills, pill packs, tablets, envelopes (containing both solids, gels or even liquids), dispensers, aspirators, etc.) through a secure, tamper-proof medication storage and dispensing unit 104, which will dispense individual doses sequentially only after strict user identification (ID) requirements are met through the use of one or more ID establishing components in the control unit 102. These user ID requirements may include components capable of establishing and/or confirming user biometrics (including but not limited to ID determination for Face recognition, fingerprint, voice recognition and others), Global Positioning (GPS) location, as well as through cellular/wireless internet location, and traditional security such as passwords, two factor authentication, Personal Identification Numbers (PIN), authorized medical personnel approval after voice/video interaction and others. Each dispensed dose will be tracked and logged (including time and frequency), in order to decreasing both access and medication misuse.

The above may be accomplished through a user interface screen or combination screen/keypad **106**, a fingerprint scanner **108**, a camera **110** and speaker/microphone (built anywhere convenient within the control unit **102**. One or more computer processors and memory electronics network interface components are also built within the unit **102**, including internet of things (IoT) interface electronics (including but not limited to Radio Frequency Identification (RFID), Internet awareness (including Internet Interface I/F, network identification, messaging, email, website I/F, etc.), as well as programming so the device may be interfaced to via Wi-Fi, Bluetooth, Wireless Internet (such as 4G, 5G and other wide area protocols), WhatsApp, SMS messaging, Facebook Messaging, etc. In one embodiment, the control and/or dispensing units may be externally powered and/or have internal energy storage components (batteries, backup batteries, etc.).

The central unit **102** may be configured to allow medication tracking and/or reordering using a network. The network may be the Internet or some other network allowing for communication between the system **100** and an ordering/reordering/dispensing facility (e.g. a pharmacy, medical dispensing facility, authorized medication dispensary, etc.). In addition to reordering, the time and day of each medication dispensing may be logged and communicated to a medical supervising authority (such as Pharmacist, Pharmacist Assistant, Physician, hospital or insurance company or any such legally authorized medication dispensing entity).

In one embodiment, the central unit **102** has a touch screen **106** that allows a user to navigate through a graphical user interface that control operation of the dispenser system **104** and related functions. The user interface may include automated operation (via Biometrics, etc., or PIN, or password), or it may require video/voice interface with a supervisory agent across the internet and/or telephonic network.

The control unit **102**, is thus a stand-alone unit capable of interfacing both with the user, as well as the user's portable electronics such as cellphone, smartphone, Tablet, Personal Computer (PC), terminal, Smartwatch, etc. AND with a medical dispensing control organization (e.g. Pharmacy, Medical Plan, Doctor's Office, Legal Authorities or their proxies, etc.). In this fashion, the control unit **102** acts as an interface medium to the authorized device user or patient. Utilizing a secure network, the control unit will transmit patient usage information to a central database within the cloud, keeping track of the time of day and amount dispensed will greatly help in the ability for institutions to understand and develop new pain management protocols. In one embodiment, the interface and communication between the control unit **102** and the one or more dispensing units **104**, and/or the interface and communication between the control unit **102** and any remotely located supervisory/management entities (e.g. pharmacist, nurses, doctors and others) is over a secure channel.

FIGS. 3-4 illustrates the interface between the control unit **102** and the transporting/storage/dispensing unit **104**. One or more guide pins, locking mechanism or alignment fixtures **202/204** are used to align the units to each other, and one or more system interface electronic components **302** are used to connect the control **102** to the one or more dispensing units **104**. These system interface electronics may be wired or wireless and may include simple power (both directly connected via wiring and/or induced voltage receiver (bypassing the need to connect) for power and/or battery recharging and/or combinations thereof. Similarly, the wiring may be used for electronic signal transfer (e.g. USB, Firewire and other Interfaces), as well wireless communi-

cation between the control unit **102** and the dispensing units **104**, such as Wi-Fi, Bluetooth and others. In one embodiment, the dispensing unit **104** is designed to be sealed (with only the primary opening having access to the interior) and tamper-proof, so that it may be even shipped via postal/courier service while filled with high value/risk prescriptions.

The profile for one or more patients is entered/confirmed onto the control unit, and it is coupled with the unique ID of the one or more dispensing units **102** (say a 1st one for one patient and a second for another). Thus in one embodiment, the patient takes a secured and/or locked medication dispensing tray **104** home, and then coupled electrically and/or electronically to the control unit **102**.

In one embodiment, once the user is authenticated (via video call, biometric validation, password or other suitable form) by validating the patient, the drug and the medication dosage, the dispensing unit **104**, proceeds to be activated and the medication is dispensed via the opening or dispensing slot **402**. In one embodiment **100**, this is accomplished by mating the dispenser **104** to the control unit **102**, in another, this is accomplished by having the dispensing unit be also the control unit FIG. **12**. In yet another embodiment, the control unit **102** is an app within a Smartphone that is connected via wireless to the dispensing unit **104** such as FIG. **11** so that validation of the user is carried out through the screen, camera and biometrics/authentication components connected to the phone. In addition, we see a lockable case **204** and key. In all cases above, no dispensing is done without satisfying the medical authorities and their approved proxies/delegates.

FIGS. 5-8 illustrate the internals of the dispensing unit **104**, which include dispensing electronics **502** which control the rotation of the dispensing wheel **504**. The wheel **504** has two or more cavities **510** formed by the paddles **512** along it's periphery. Said wheel **504** is housed, surrounded, enclosed within a cylinder **514**, the cavity forms a sealed void which is only accessible to the outside when lined up with the dispensing slot or opening **402**. That is, the medication will stay within the cavity until the wheel rotates and aligns with it, at which point it drops via gravity **700**.

In one embodiment, there is a dispensing sensor **506**, so that there may be a positive detection of the cavity's content flowing outbound via the slot **402**. The wheel **504** is advanced via a control signal from the electronics **502** which activate wheel rotation components. Said wheel rotation components may be comprised of one or a combination of electrical, pneumatic, spring or other suitable motors or actuator. In one embodiment, a worm drive motor **508** coupled (FIG. **6**) to a set of gearing teeth **602** along the periphery is preferred, since those skilled in the art will appreciate that a worm drive is very hard to move through mechanical 'pushing' by fingers or other tools via the slot **402**. (Something that users or others may attempt to do in order to obtain an unauthorized dose).

Do note, that the worm drive does not preclude the operation of the wheel **504** in either direction, something that may be advantageous when refilling a wheel that has some medication left in it. Similarly, one or more portions of the sides **702** of the dispensing unit **104** may be made translucent or transparent, so that the number of wheel **504** slots **510** still having medication may be ascertained.

In one embodiment, the dispensing unit **104** may have one or more sides openable **702** via keys or locks, or even via an internal lock that only releases under the acknowledgement of an authorized medical authority. This would provide a tamper-proof enclosure **104**. In another embodiment, the

dispensing unit **104** be sealed, so that access to the interior is controlled through the one or more entries (the slot **402**) for both entry and exit of the medications.

FIGS. **9-10** illustrate a proposed refill solution **900**. In this, an authorized entity (pharmacy, medical distributor or logistic agency such as Amazon) need only reverse the process of filling. That is, have a special control unit **902** programmed to control a dispensing unit **104** that is nested within it (via the alignment of fixture(s) **906** to fixture **202/204**) so that the feeding the hopper **904** with medication, results in the medication dropping into the cavity. In one embodiment, the passing of the medication into the cavity is noticed by the sensor **506** within the dispensing unit **104**, and the load control unit **902** advances the wheel **504**. In another embodiment **1000**, a sensor **1002** is mounted within the hopper **902** to confirm/detect the medication entry into the dispensing unit **104**. The wheel **504** every time the appropriate cavity load (typically a prescription dose) receives the dose. This may be detected via an external sensor **1002**, or via the confirmation from the internal sensor **506**.

In an alternate embodiment, where live monitoring is required/desired, once the patient submits their biometrics to the unit **102**, there is an additional step where the provider will verify through telemedicine the patient ID/information/person and dispense the medication via a secure network.

FIG. **13** illustrates the flowchart of a proposed embodiment, showing the system operation. Any attempt to access medication outside of prescriber's intention will automatically be transmitted to the provider, including the biometrics of anyone that has attempted to open the unit **102** but has failed to be authenticated. Even for registered patients, if the patient does not have a prescription in the system, we see the process end.

While presently dispensing and distribution of certain medication is limited to licensed pharmacies, it is interesting to see how the delivery of even licensed medications could be expanded by the use of the dispensing unit **104** proposed. Services such as AMAZON LOCKERS could be used to ensure that the dispensing unit **104** is positively delivered to the authorized user, who would still be limited to access the medication within the unit to the approved biometric/visual/PIN/password channels.

In an exemplary embodiment of the invention, the control unit **102** controls the dispensing of controlled pharmaceutical agents within the tamper-proof dispensing unit **104** located in a remote location, so that the medication is not available to the patient all at once, but dispensed directly to the patient as prescribed by the physician and only available to that patient at the time and dosage interval prescribed. For certain patients, the process may be biometric but not monitored in real time (although all deliveries are logged in time). In these, dispensing requires a biometric date from the patient to assure the prescribed pharmaceutical agent is only delivered to that patient and in the dose prescribed on the allowable dates and/or the allowable intervals for a given prescription.

In an alternate embodiment, every delivery to the patient is monitored through video as well as through biometrics, so that conditions may be judged and/or recorded. Both the control unit **102** and the dispensing unit **104** are strong enough to prevent unauthorized tampering, as well as to demonstrate any tampering with them. In this fashion, when the uniquely identified dispensing units **104** are sent back/forth to the pharmacy/dispensary, they are scanned for unauthorized access attempts.

By having the ability for the controlled administering and monitoring of controlled pharmaceutical agents through secure channels for compliance and tamper detection, unauthorized opening is both prevented and recorded with legal repercussions. The information/data about the person operating the device and/or receiving the dispensed dose is received over a secure data channel for the purpose of modifying the time or dosage by the prescribing physician.

In one embodiment, the device has video/audio capabilities, so that the identify and actions of the patient, and their compliance with any instructions can be monitored in real and/or delayed mode. This provides a method for preventing unauthorized dispensing of a controlled substance by matching patient biometric data with the prescription.

In one embodiment, the invention allows for the secure transportation, including shipping of the container having the medication to the patient, who can then, using pre-stored biometrics have the device dispense the medication. In another, the device is registered to the user biometrics' when in audio/video communication with an authorized agent, and/or when in the presence of license/authorized personnel.

Notice when we say biometrics, we refer to fingerprint, facial recognition, voice or sound recognition, and/or any other method in which we can uniquely identify a human being. In addition to recording the correct ID, the unit will record the times and identities of any failed access (be it because the person's ID fails, too many attempts. Off-times and/or other unauthorized access attempts).

In an alternative embodiment, the system may be provided with security features to help limit unauthorized or inappropriate dispensing of medication. As such, the system establishes the ID of the person operating it, so as to prevent unprescribed users from having medication delivered to them. The medication placed within the cavities **502** may be pre-packaged in child safe (or child resistant) form. When ANY tampering or dubious access attempts are recorded, the control unit **102** may be configured so as not to dispense a medication dose until the appropriate measures are taken to reactivate the unit.

The dispenser unit **104** may have an RFID ID chip, to ensure that the unit is recognized by the control unit **102**. The system may have the ability to key a specific electronic device, such as a cell phone, to a specific user and the dispenser system may require the electronic device to be within proximity of the dispenser system before dispensing medication for that user. The dispenser system may determine the proximity of the keyed electronic device using capabilities associated with Bluetooth, Wi-Fi, Near Field Communications or other wireless methods and apparatus. For example, during set up, a user may be keyed to a specific smart phone. The dispenser system may be configured to search for the smart phone to be within sufficient proximity before dispensing any pills.

To better illustrate the many applications of the system, we illustrate a one exemplary embodiment in the example below:

Example 1

1. A patient arrives at the pharmacy with a prescription for a controlled substance that requires further protection.
2. The patient's profile is applied to the prescription by the pharmacist. If the patient profile does not exist patient biometrics are added to system, by an authorized person.
3. Once patient biometrics are verified the pharmacist will fill the dispensing unit **104** with the medication for the prescription, or a unit **104** may have been previously loaded.

4. Patient biometrics and patient profile are added to the memory on both the cloud and the dispensing unit electronics **104**.

5. Once the dispensing unit **104** is interfaced to the control unit **102**, the information is either confirmed via the web/cloud, or the information within the dispensing unit is confirmed with that held in the control unit **102**.

6. Once the patient is ready for their first dose or subsequent doses, they will submit their biometrics to the device for authentication.

7. The device will determine whether or not adequate amount of time has passed for the patient to receive their next dose. If the dose is not ready, it will indicate how much time remains before the patient is allowed to access their next dose. If an adequate amount of time has passed it will automatically dispense the prescribed amount of medication.

8. If further monitoring is needed, video confirmation will prompt the patient to submit their patient biometrics to the device, which will in turn submit the patient profile to a telemedicine provider and the telemedicine provider will be able to dispense a dose by a secure network to the patient.

9. Patient use statistics will be sent to a database by a secure network in order to better monitor medication compliance for better pain management and future medication protocols.

10. Once the prescription time comes near an end, or has ended, the control unit **104** automatically notifies the cloud and the process is repeated.

11. The patient will bring either the dispensing unit **104** back to the pharmacy to be refilled, or bring the entire medication delivery system back to the pharmacy so that the unused medication is not allowing it to be disseminated illegally.

14. Once the medication tray and/or medication dispenser have been received by the pharmacy, the pharmacy will be able to repeat step one in order to determine whether or not a refill is required or the prescription has been completed.

CONCLUSION

In concluding the detailed description, it should be noted that it would be obvious to those skilled in the art that many variations and modifications can be made to the preferred embodiment without substantially departing from the principles of the present invention. Also, such variations and modifications are intended to be included herein within the scope of the present invention as set forth in the appended claims. Further, in the claims hereafter, the structures, materials, acts and equivalents of all means or step-plus function elements are intended to include any structure, materials or acts for performing their cited functions.

It should be emphasized that the above-described embodiments of the present invention, particularly any "preferred embodiments" are merely possible examples of the implementations, merely set forth for a clear understanding of the

principles of the invention. Any variations and modifications may be made to the above-described embodiments of the invention without departing substantially from the spirit of the principles of the invention. All such modifications and variations are intended to be included herein within the scope of the disclosure and present invention and protected by the following claims.

The present invention has been described in sufficient detail with a certain degree of particularity. The utilities thereof are appreciated by those skilled in the art. It is understood to those skilled in the art that the present disclosure of embodiments has been made by way of examples only and that numerous changes in the arrangement and combination of parts may be resorted to without departing from the spirit and scope of the invention as claimed. Accordingly, the scope of the present invention is defined by the appended claims rather than the foregoing description of embodiments.

The invention claimed is:

1. A method for controlled access medication dispensing, said method comprising;
 - providing a tamper-resistant medication storage and dispensing unit equipped with internal medication storage and dispensing components, wherein said medication storage and dispensing unit is comprised of an enclosed wheel within a housing having only one outside opening, and said wheel is mechanically linked with wheel rotation components;
 - said wheel having two or more cavities, so that rotation of said wheel by said rotation components causes one said cavity at a time to align with a smooth and unobstructed medication dispensing chute connected directly to said single outside opening in said unit;
 - said opening providing access for loading medication into said dispensing unit's interior, as well as for dispensing medication outside said dispensing unit's interior and electronic interface components to control said internal medication component, including storing patient prescription, patient identification and stored medication information by authorized medical authorities or personnel;
 - said wheel rotation components are selected from a combination of one or more of:
 - a worm drive motor, stepper motor, servo motor, mechanical clock mechanism or such other;
 - said rotation component is coupled to one or more gearing teeth on said wheel; and
 - said enclosed wheel can only be moved while said wheel rotation component is engaged;
 - there is a dispensing sensor on said dispensing slot;
 - said housing is sealed; and
 - a refilling unit configured to drop medication via said dispensing unit's opening and automatically advancing the dispensing wheel within the dispensing unit.

* * * * *